

FENCER

POSTDRIVER

FEATURES

- Heavy 230kg hammer standard
- Hydraulic side tilt
- Hydraulic top link
- 4m Tribeam mast - unique reinforcing technology
- Mega Flow hydraulic system
- Heavy duty post cap and locator pin
- 3pt linkage rear mounted
- Heavy duty base with wide support feet
- Cat 1 & 2 linkage



SPECS

The Fencer Postdriver is a mid range machine built Fieldmaster tough. Featuring strong, tri beam mast and complete with hydraulic side tilt and top link as standard.

Also available as a 'combo' unit with the outstanding hydraside shift base to make working days easier. The 'Fencer' is best suited for larger farms and fencing professionals.



FENCER POST DRIVER

THE FIELDMASTER POSTRAMMER RANGE - FARMER - FENCER - FORTE

STANDARD SPECIFICATIONS

STD MAST LENGTH	4.0M
WEIGHT (INCL HAMMER)	505KG
STANDARD HAMMER WEIGHT	230KG
SIDE TILT OPERATION	HYDRAULIC
TOP LINK OPERATION	HYDRAULIC
LINKAGE MOUNTING	CAT 1 + 2
MOUNTING POSITION	REAR 3PT LINKAGE
HEIGHT UNDER HAMMER (4M)	3700MM
HEIGHT UNDER HAMMER (4.5M)	4200MM
MIN RECOMMENDED PSI(MAX)	1800PSI (3000PSI)
MIN HYD FLOW	18L/MIN (60L/MIN)
SIDE TILT ANGLE (L TO R)	20/20
TOP LINK ANGLE (FWD/BACK)	20/28

OPTIONS

- Heavy 280kg hammer weight
- Hydraulic side angle/tilt kit
- 4.5M Folding mast
- Side shift hydraulic nudge ram kit
- Hydraulic rock spike and extractor kit
- Hydraulic pilot auger kit
- Extra hyd valve banks
- Closed circuit hyd valve system
- Polypropylene post cap insert
- Excavator mounting frame
- Operator safety guard